



Main features

Printing type



Barcode



Logos



Alphanumeric text

Maximum height



0-15 mm



16-100 mm



Above 100 mm

Printing surfaces



Primary packaging



Secondary packaging



Raw material

- Ergonomic industrial stainless steel IP65 cabinet protected against water jet, vapor and dust (plant air required).
- Up to 5 lines with characters height from .032" - .56" (.8 - 14 mm) with micro print nozzle for high resolution print.
- Real-time production calculation and download on USB key for production reports.
- Interconnected: module "Serial Interpreter" decodes and converts the information coming from external devices as ERP, PLC, scale, scanner, labeling systems.
- Complete remote control and monitoring of the printer.

Z5700

TECHNICAL SPECIFICATION

PRINTING CHARACTERISTICS

- Up to 5 lines of print
- Characters height from .032" – .56" (.8 - 14 mm)
- Line speed capability: up to 400 mt/min (1320 ft/min)
- Print rate: up to 2136 ct/sec
- Messages and logos storage: up to 4 GB with expandable micro SD memory
- Up to 6800 stroke per message
- Fixed and variable text field types (with operator, automatic or external)
- Text field placing is freely selectable
- Available fonts: 5x4, 5x5, 7x4, 7x5, 9x7, 10x8, 16x10, 24x16, 32x18 and Windows True Type
- Space between characters is freely selectable
- Print intensity is freely selectable
- Rapid images, shapes and lines creation from touch-screen display
- Automatic date, time, offsets and expiry date multifunction
- Incrementing/decreasing alphanumeric product counters up to 9 digits
- Metric repeat print – message function
- Customizable message repeat with single print start
- Field orientation: 0°, 90°, 180°, 270°
- Tower print function (Text rotation of 90°)
- Coding throw distance up to 3.54" (90 mm)
- Single line from min. .118" (3 mm)

BAR CODES

- 2/5 Industrial, UPC-A, CODE 39, EAN 13, CODE 128 (A,B,C), EAN 128 (A,B,C), 2D - Datamatrix, ITF (A,B,C), QR Code

CONTROL UNIT CHARACTERISTICS

- 10.1" TFT full color anti-reflection high contrast LED touch-screen
- Stainless steel structure AISI 304
- IP65 rating (plant air required)
- Conduit length: 2 mt – 6.6 ft (4 mt – 13.1 ft optional)

GENERAL FEATURES

- Exclusive customizable user interface for single operator (functionality, language and alphabets)
- Intuitive user interface with graphic icons
- Innovative graphic editor with stretch and drag & drop functions with smartphone technology
- User interface and virtual keyboard with foreign languages and alphabets
- Automatic flushing with solvent recycling in both start up and shut down
- Low consumption thanks to the enhanced recycling system
- Message storage with file name
- Print parameters storage in the messages

- Check message dimension
- Multi-level access with login
- Report function for executed printing counter
- On line help and user manual with contextual photos and videos

PRINTHEAD

- Stainless steel and aluminium structure hermetically sealed
- Micro Print Nozzle for high quality resolution print (optional)
- Auto-phasing of ink stream for consistent print quality
- Microjet nozzle cleaning function
- Wide range of standard, pigmented, food, BIODEgradable and MEK-free inks
- Conduit inlet at 90° (optional)
- Internal Supply Positive Air Function
- 90° model for reduced/short spaces (optional)

EXTERNAL CONNECTIONS

- Serial connection RS232 and RS485/422
- Ethernet interface for LAN 10/100 connection
- USB port version 2.0
- Sensor management for product reading
- System ready output
- Shaft Encoder input for variable speed production lines
- External alarm outputs with traffic light column
- Parallel interface BCD, 6 bit
- Scanner connection for printed bar code validation or index message selection
- Dry air kit (plant air required)

ENVIRONMENT/ELECTRICAL REQUIREMENTS

- Temperature: from 40° - 113°F (5° to 45°C)
- Humidity: 10 - 90% (non-condensing)
- Single Phase, 85 - 240 Vac, 50 - 60 Hz, 100 VA



Use a QR code reader to see the product page

Zanasi USA

9490 Hemlock Lane No.,
Maple Grove, Mn 55369
Phone: 763-593-1907
Fax: 763-593-1941
info@zanasiusa.com
www.zanasiusa.com

